

Simple Sleeper

Disassembly Instructions

The Simple Sleeper is a unique and fresh approach to the standard sleeper. It provides numerous options to suit any situation. The Simple Sleeper is offered with or without arms, casters or standard post legs, and an under mount storage system. The lightweight steel support frame and components not only provide superior strength and durability, but also recyclability.

Recyclable Material (lbs)



steel support frame	58.10
steel back frame (qty. 2)	13.30
steel tube legs (qty. 4)	14.80
steel arm frame (qty. 2)	7.30
steel armature in arm (qty. 2)	1.02
particle board in base	26.00
wood drawer assembly	96.90
wood arm cap (qty. 2)	1.78

Total Weight

219.20

*values based on a Sleeper with arms and drawers.



Page: 1 of 2

Tools: Phillips head or Robertson screwdriver, 3/4" socket wrench, box cutter knife, hammer or rubber mallet, pliers.


Skill Set: Good manual dexterity.

Estimated Time: 40min

Steps:

1. Seat Cushion - 1min

Flip the back rest panels up into the upright position to access the whole seat cushion. Locate the plastic clip at the rear underside of the Sleeper and un-clip.



2. Back - 4min

Turn the chair upside down to access the underside of the seat. Locate the four fasteners located on the underside of the seat and unfasten (screw corresponds with tube housings). Lift the back panel upward to remove. Repeat process to the second back.

3. Storage Unit (if applicable) - 10min

Drawers - Pull drawers open to full extension. Locate the release mechanism on both drawer slides. Engage the release mechanism and pull the drawer forward until completely detached from unit. Locate and remove all fasteners from the drawer slides and handle.




Storage Frame - On the roof of the storage cavity (underside of seat), locate all fasteners. Unfasten with the required screwdriver, and remove the storage frame from the Sleeper. (Caution - Storage frame may fall when unfastening. Two or more people are recommended for this procedure).

4. Armrest and Arm Panel (if applicable) - 5min


Grip the armrest cap and push backwards (front to back) and then up. In doing so the arm cap will detach from the arm rest panel. Locate the fasteners on the steel bracket and remove. At the base of the arm panel, make an incision with a box cutter

or knife at the front and back. Tear the upholstery until two fasteners are exposed at each end. With the required screwdriver, unfasten screws from metal tube. Once again, with a box cutter or knife make an incision around the perimeter of the armrest panel approximately 1/2" from its base. Remove the armrest panel by pulling out from the sleeper frame. In the event that the arm rest is unable to be removed freely, a rubber mallet or hammer may be used to tap it out.



5. Casters - 2min

Flip the Sleeper upside down to access bottoms of casters. With the required 3/4" socket wrench, locate and unfasten the central bolt. Remove the caster from the leg tube. Repeat process to the remaining casters.



Family:



Simple Sleeper (Armless)



Simple Sleeper (With Arms and Drawers)

SimpleSleeper

Disassembly Instructions

Page: 2 of 2

Tools: Phillips head or Robertson screwdriver, box cutter knife, hammer or rubber mallet, pliers.

Skill Set: Good manual dexterity.

Estimated Time: 40min per sleeper. 5

6. Sleeper Frame - 10min

With the Sleeper assembly still in the upside down position, remove the upholstery staples around the perimeter of the frame with pliers. Pull away fabric from frame to reveal a series of fasteners. With the required screwdriver, unfasten and remove screws.

7. Upholstered components. - 5min

Seat Cushion - locate the central running zipper on the underside of the seat cushion. Unzip the zipper to full length and remove the upholstery cover from the inner foam.

Back - Locate the staple line at the base of the back panel. With pliers, grasp a section of upholstery along the seam and pull firmly to separate from staples and wood backing.

Visit Spec's green news page at specfurniture.com and click on "End of Product Life Options" for recycling and biodegradation facilities near you.

Tablet

The Tablet accessory is integrated into the sleeper frame. For disassembly, remove the tablet surface at the beginning of the Sleeper disassembly. To remove, locate the 6 fasteners on the underside of the tablet and unscrew. Remove the caster and glide during step 5 - Casters, of disassembly.



Armrest

Two options of both wood or ply armrests are available in the Sleeper design. The disassembly procedure will be the same for both products. See step 5 - Arm Rest and Arm Panel, of disassembly instructions to remove. Recycling options are available for wood options only.



Family:



Simple Sleeper (Armless)



Simple Sleeper (With Arms and Drawers)